



---

Reference Document	Document No.	LINDEN-SPE-7104
Title	Cable Spec – Hybrid (-041)	

## Cable Specification

Item No.	Component	Details
1	Cable OD	6.4 mm (0.25")
2	Cable OD Tolerance	±0.3mm (0.01")
3	Fiber	1 x Singlemode STFOC (LINDEN-SPE-7034)
4	Jacket	Linden Proprietary Design; Primary strength coating: LCP/Vectran Braid/Polyester
5	Attenuation @ 1310 nm (dB/km)	< 0.5
6	Attenuation @ 1550 nm (dB/km)	< 0.5
7	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
8	Number of Conductors	Two (2)
9	Conductor Gauge	20 AWG
10	Tensile Strength (lbs)	880 lbs
11	Serialization	All cables will have Cable ID number for traceability
12	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 6.4mm (2-CU-1-FO-O-155-Q-250)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)