



Reference Document	Document No.	LINDEN-SPE-7125
Title	Cable Spec – Hybrid (-072)	

Cable Specification

Item No.	Component	Details
1	Cable OD	14.1 mm (0.557")
2	Cable OD Tolerance	± 0.3 mm (0.01")
3	Fiber	2 x Singlemode STFOC (LINDEN-SPE-7043)
4	Jacket	Linden Proprietary Design; Primary strength coating: STFOC/Aluminum-Polyester Tape Wrap/TPU/Aramid Braid/TPE
5	Attenuation @ 1310 nm (dB/km)	< 0.5
6	Attenuation @ 1550 nm (dB/km)	< 0.5
7	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
8	Number of Conductors	Two (2)
9	Conductor Gauge	16 AWG
10	Calculated SG	1
11	Tensile Strength (lbs)	1,200
12	Serialization	All cables will have Cable ID number for traceability
13	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 14.1mm (2-CU-2-FO-Q-557)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)