Linden Photonics, Inc.

Purpose-Built Cables

PRISM AWARDS WINNER

Reference Document	Document No.	LINDEN-SPE-7589
Title	Cable Spec – Copper (-541)	

Cable Specification

Item No.	Component	Details
1	Cable OD nom.	14.6 mm (0.573”)
2	Fiber	None
3	Jacket	Linden Proprietary Design; PVC/PE/Mylar Tape/Aramid Braid/TPU
4	Attenuation @ 1310 nm (dB/km)	N/A
5	Attenuation @ 1550 nm (dB/km)	N/A
6	Optical Propagation Loss Measurements	N/A
7	Number of Conductors	Two (2) x # 24
8	Conductor Gauge	#24 AWG (19/36) & One (1) x RG-58 Type Coax
9	Voltage Rating	300V
10	Resistance	21.4 Ω/1,000 ft
11	Tensile Strength (lbs)	1,200
12	Safe Working Load (SWL)	Recommended guideline - 15% (180 lbs); SWL is application and environment dependent
13	Minimum Bend Radius (MBR)	Recommended guideline - 291 mm (11.5”); MBR is application and environment dependent
14	Weight in Air (g/m)	168
15	Operating Temperature (°C)	-55 to 80
16	Serialization	All cables will have Cable ID number for traceability

OD (P/N): 14.6 mm (3-CU-O-393-FQ-573)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)