Linden Photonics, Inc.

Purpose-Built Cables

PRISM AWARDS WINNER

Reference Document	Document No.	LINDEN-SPE-7567
Title	Cable Spec – Hybrid (-519)	

Cable Specification

Item No.	Component	Details
1	Cable OD	6.1 mm (0.240”)
2	Fiber	1 x Singlemode STFOC (LINDEN-SPE-7034)
3	Jacket	Linden Proprietary Design; Primary strength coating: STFOC/Vectran Braid/TPU
4	Attenuation @ 1310 nm (dB/km)	< 0.5
5	Attenuation @ 1550 nm (dB/km)	< 0.5
6	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
7	Number of Conductors	Two (2)
8	Conductor Gauge	22 AWG (M22759/19-22)
9	Voltage Rating	600 V
10	Cable Weight (lbs./1,000 ft.)	20
11	Tensile Strength (lbs)	1,600
12	Safe Working Load (SWL)	Recommended guideline - 15% (240 lbs); SWL is application and environment dependent
13	Minimum Bend Radius (MBR)	Recommended guideline - 122 mm (4.8”); MBR is application and environment dependent
14	Serialization	All cables will have Cable ID number for traceability
15	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 6.1 mm (1-FO-2-CU-O-151-FQ-240)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)