Linden Photonics, Inc.

Purpose-Built Cables

PRISM AWARDS WINNER

Reference Document	Document No.	LINDEN-SPE-7583
Title	Cable Spec – High Strength (-535)	

Cable Specification

Item No.	Component	Details
1	Cable OD	13.3 mm (0.525”) nom.
2	Fiber	1 x 2-ch Singlemode (LINDEN-SPE-7283)
3	Jacket	Linden Proprietary Design; PA/HDPE/Aramid/TPU
4	Attenuation @ 1310 nm (dB/km)	< 0.5
5	Attenuation @ 1550 nm (dB/km)	< 0.5
6	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
7	Tensile Strength (lbs)	12,000 lbs
8	Safe Working Load (SWL)	Recommended guideline - 15% (1,800 lbs); SWL is application and environment dependent
9	Minimum Bend Radius (MBR)	Recommended guideline - 267 mm (10.5”); MBR is application and environment dependent
10	Nom. Weight in Air	160 kg/km
11	Serialization	All cables will have Cable ID number for traceability
12	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 13.3mm (2-SM-V-63-T-281-Q-525)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)